

JEMT

Journal of Earth and Marine Technology homepage URL: ejurnal.itats.ac.id/jemt



Groundwater quality in Ponjong Karst, Gunungkidul Regency, Special Region of Yogyakarta

Avellyn Shintya Sari ^{1,2}, Sari Bahagiarti K. ², Suharsono ², C. Prasetyadi ² ¹ Department of Mining Engineering, Institut Teknologi Adhi Tama Surabaya ² Department of Geological Engineering, Faculty of Mineral Technology, University of Penmbangunan Nasional "Veteran" Yogyakarta e-mail: <u>avellyn@itats.ac.id</u> DOI: 10.31284/j.jemt.2020.v1i1.1142

| Article info | Abstract |
|---------------------|---|
| Received: | The hydrogeological condition of a region is determined by the type of |
| 12 May 2020 | lithology, morphology, and subsurface conditions where the condition is |
| Revised: | very helpful in the study of groundwater exploration. Especially when we |
| 10 August 2020 | encounter interesting geological conditions when the groundwater |
| Accepted: | exploration in the karst area in which volcanic rocks are resulting from the |
| 15 August 2020 | activities of the active volcano in the past. Groundwater exploration at |
| Published: | Ponjong area and surrounding does have its special characteristics, because |
| 3 September 2020 | it has 2 different rock characteristics where the northern part of the research |
| | area in the form of a karst area (limestone of Wonosari Formation) while the |
| Keywords: | southern part is an area of ancient volcanoes with dominant volcanic rocks |
| groundwater, karst, | from Wuni Formation, As for the research on the above and subsurface |
| hydrogeology | research area where the research is conducted based on surface geology |
| | mapping, geoelectric data collection, and groundwater sampling. Geological |
| | mapping includes geomorphological data, stratigraphy, and geological |
| | structure. The aquifer system of the research area can be divided into two |
| | systems, inter-grain aquifer systems, and fracture aquifer systems. Overall |
| | quality groundwater in the research area is quite good. Ponjong District there |
| | are mining activities that have resulted in changes in the land use system in |
| | the area. This can cause changes in the water surplus in the area due to the |
| | changing catchment area. |

1. Introduction

Hydrogeological conditions of a region are determined by the type of lithology, morphology, and subsurface conditions where the condition is very helpful in the study of groundwater exploration. Especially when we encounter interesting geological conditions when the exploration of groundwater in the karst area in which volcanic rocks are resulting from the activity of mount active fire in the past. Judging from the availability of groundwater, not all rocks in Gunungkidul Regency, especially Ponjong Districts have aquifers. While the area with good groundwater condition is bad depends on permeability. Groundwater exploration in Ponjong District does have its special characteristics, while the research here uses top and bottom surface research where the research was conducted based on surface geology mapping, data collection, and groundwater sampling. Geological mapping includes geomorphological data, stratigraphy, and geological structure. Study Area Located in Ponjong District, Gunungkidul Regency, Yogyakarta, Indonesia (Figure 1).

Limestone mining activities large and small scale are still the biggest threat to the preservation of karst areas. The destruction of limestone mining can be seen in the karst landscape appearance. The hills will be cut in many places. The mining process by dredging the karst area is taking the main part of water storage in the karst hills and damaging the existing hydrological system. The impact that occurs is an increase in the quality and quantity of water demand as well as a decrease in water availability in terms of quality and quantity in the area of land conversion.



Figure 1. The study area

2. Methodology

This research was conducted based on surface geology mapping, data collection, and groundwater sampling. Geological mapping includes geomorphological data, stratigraphy, and structural geology.

3. Result and discussion

Groundwater exploration at the Ponjong area and surrounding does have its special characteristics because it has 2 different rock characteristics where the northern part of the research area in the form of karst area (limestone of Wonosari Formation). Formation (Figure 4).



Figure 2. The location of Ponjong Karst



Figure 3. Model aquifer typology: (a) Typology of aquifer system of volcanic sediments [1], (b) Typology of alluvial sedimentary aquifer systems, (c) Typology of sedimentary aquifer systems, (d) Typology of crystalline aquifer systems [2], (e) Typology of a folded sedimentary aquifer system, (f) Aquifer typology of karst [3]



Figure 4. Groundwater Basin of Gunungkidul Regency (left) [4], Stratigraphy of Study Area (right) [5]

3.1. Chemical water quality in limestone

Limestone is a sedimentary rock [6]that is chemically composed of calcium carbonate (CaCO3). Based on laboratory tests, limestone contains ingredients as shown in table 1 below.

| | Sample code | Laboratory analysis | | | | | | | | |
|-----|----------------|--|-------------------|---------------|------|--------------|-----------------|--------------|--------------|--|
| No. | | X = East Y = North Z = Elevasi | DHL (Umhos/Cm) | TDS (mg/l) | рН | Fe (mg/l) | CaCO3 (mg/l) | Ca (mg/l) | Mg (mg/l) | |
| 1. | SM 01 | X = 0468355 Y = 9114414 Z = 311 | 408 | 196 | 6,77 | 0,07 | 145,5 | 11,64 | 27,936 | |
| 2. | SM 02 | X = 0468418 Y = 9114397 Z = 307 | 760 | 370 | 6,61 | 0,06 | 212,43 | 52,768 | 19,3224 | |
| 3. | SM 03 | X = 0468469 Y = 9114438 Z = 307 | 627 | 304 | 6,73 | 0,03 | 172,66 | 48,8888 | 42,292 | |
| 4. | SM 04 | X = 0468543 Y = 9114393 Z = 310 | 430 | 208 | 6,75 | 0,02 | 142,56 | 42,292 | 9,0792 | |
| 5. | SM 05 | X = 0468330 Y = 9118330 Z = 312 | 487 | 236 | 6,83 | 0,01 | 129,98 | 26,772 | 15,132 | |
| 6. | SM 06 | X = 0468269 Y = 9114084 Z = 305 | 521 | 252 | 6,61 | 0,00 | 193,03 | 61,304 | 9,5448 | |
| 7. | SM 07 | X = 0467670 Y = 9114182 Z = 276 | 345 | 166,2 | 7,01 | 0,02 | 148,41 | 28,712 | 18,3912 | |
| 8. | SM 08 | X = 0467425 Y = 9113790 Z = 285 | 427 | 206 | 6,69 | 0,06 | 142,59 | 32,204 | 14,8992 | |
| 9. | SM 09 | X = 0469586 Y = 9114348 Z = 353 X = 0469550 | 577 | 280 | 6,89 | 0,00 | 141,62 | 7,76 | 29,3328 | |
| 10. | SM 10 | X = 0469659 Y = 9114273 Z = 351 | 437 | 211 | 6,53 | 0,02 | 202,73 | 29,876 | 30,7296 | |
| 11. | SM 11 | X = 0469339 Y = 9119339 Z = 346 | 505 | 244 | 6,89 | 0,00 | 203,7 | 6,984 | 44,6976 | |

Table 1. Limestone chemical analysis laboratory Ponjong District

| Table 2. Water quality criteria of class B | | | | | | | | |
|--|--------------------------------|----------|----|--------------------------------|---------|---------------|--|--|
| No Parameters | | Average | No | Parameters | Unit | Maximum value | | |
| | | (%) | 1 | Physical | | | | |
| 1 | SiO ₂ | 0.048571 | а | Total dissolved (TDS) mg/l | | 1.000 | | |
| 2 | Al_2O_3 | 0.16587 | b | Temperature | °C | Deviation 3 | | |
| 3 | Fe ₂ O ₃ | 0.123302 | 2 | Chemical | | | | |
| 4 | CaO | 54.11147 | а | pН | - | 6,5 – 9 | | |
| 5 | MgO | 0.300962 | b | Zinc (Zn^{2+}) | mg/l | 0,05 | | |
| 6 | Na ₂ O | 0.037527 | с | Fluoride (F ⁻) | mg/l | 1,5 | | |
| 7 | K ₂ O | 0.034752 | d | Arsenic (As) | mg/l | 1 | | |
| 8 | TiO ₂ | 0.028919 | e | Carbonate (CaCO ₃) | mg/l | 500 | | |
| 9 | MnO_2 | 0.0288 | f | Magnesium (Mg) | mg/l | - | | |
| 10 | P_2O_3 | 0.044258 | g | Nitrat (NO ₃₋) | mg/l | 10 | | |
| 11 | CaCO ₃ | 166.83 | h | Nitrit (NO ₂₋) | mg/l | 0,06 | | |
| 12 | MgCO ₃ | 0.600577 | i | Sulphate (SO _{4 2-}) | mg/l | 400 | | |
| 13 | H_2O | 0.775687 | j | Copper (Cu ²⁺) | mg/l | 0,02 | | |
| 14 | HD | 42.79076 | k | Chloride (Cl ⁻) | mg/l | 600 | | |
| | | | 1 | Manganese (Mn) | mg/l | - | | |
| | | | m | Iron (Fe) | mg/l | - | | |
| | | | 3 | Biology | | | | |
| | | | а | Coliform total | MPN/100 | Not pipeline | | |
| | | | | | ml | water: 50 | | |

4. Conclusions

- The aquifer species based on aquifer analyses data indicate unconfined aquifer and semi-distorted aquifers. The aquifer system of the research area can be divided into two systems, inter-grain aquifer systems, and fracture aquifer systems.
- The aquifer system of the research area can be divided into two systems, inter-grain aquifer systems, and fracture aquifer systems. Overall quality groundwater in the research area is quite good.
- The groundwater quality in the karst Ponjong can be used as an irrigation and shows a value that is safe enough for consumption by the water quality criteria of class B.

References

- [1] H. Williams, F. J. Turner, and C. M. Gilbert, "Petrography: an introduction to the study of rocks in thin sections.," *Petrogr. an Introd. to study rocks thin Sect.*, 1982.
- [2] A. M. A. S. W. dan M. Baiquni, "SLUM, SQUATTER, AND QUASI-SQUATTER HOUSING DEPRAVITY IN YOGYAKARTA," *J. Teknosains*, 2015, doi: 10.22146/teknosains.6046.
- [3] R. J. Dunham, "Classification of Carbonate Rocks According to Depositional Textures," 1962.
- [4] A. N. T., "Pemisahan Aliran Dasar Bagian Hulu Sungai Bribin pada Aliran Gua Gilap , di Kars Gunung Sewu , Gunung Kidul , Yogyakarta," *Indones. J. Geosci.*, 2011.
- [5] R. W. Van Bemmelen, "The Geology of Indonesia. General Geology of Indonesia and Adjacent Archipelagoes," *Government Printing Office, The Hague*. 1949, doi: 10.1109/VR.2018.8447558.
- [6] F. J. Pettijohn, P. E. Potter, and R. Siever, "Sand and Sandstone," Soil Sci., 1974, doi: 10.1097/00010694-197402000-00013.